

INSTALLATION MANUAL

**FLUORESCENT BATTEN FITTING
 (ANODISED ALUMINIUM MIRROR REFLECTOR)**

- MR 120 • MR 220 • AMR 120 • AMR 220
- MR 140 • MR 240 • AMR 140 • AMR 240


INSTALLATION NOTICE

Warning

- Please follow all the installation manual carefully. Any improper installation will cause burn, electrical shock and lamp malfunction.
- Please do not modify or change the actual part of the lamp
- Please ensure the incoming supply voltage in valid rating.
- If the lamp malfunction, please cut off the supply and call the qualified technician or the related store which sell this product.
- Please do not close this product with sound or heat prove material.
- Please do not install this product near to the inflammable material.

Notice

- Please do not install this product under direct sun reflected area, enclose with vaporized material & vibrating area.
- Please cut off the supply during the maintenance work.



Step 1: Open the screw from the cover.




Step 2: Insert the lampholder into the provided hole.





Step 3: Take Out starter from starter holder and attached at the prepared hole



Step 4: Insert again starter into starter holder such as indicated in picture.



Step 5: Tie the fixture on ceiling after supply wire insert inside supply hole.



Step 6: Connect the supply wire in the provided connector.



Step 7: Close the cover and place the reflector on top off the cover and screw with properly.



Step 8: Insert the tube properly and twist it 90°.

Step 3. Take Out starter from starter holder and attached at the prepared hole.